



DEM NBLNAH2304 2290-2325 MHz.

Specifications:

Gain:	23dB nominal
Noise Figure:	<0.7dB
P1dB:	+17dBm output
Input VSWR:	>6dB
Output VSWR:	>13dB @ Design Frequency
Voltage:	+7 - +22 VDC
Current Drain	220mA nominal



Description:

Our new **Narrow Band** series of low noise amplifiers shares a common design that is utilized by all LNA's between 144 and 2400 MHz. Each LNA utilizes the ultra low noise QORVO QPL9547 MMMIC coupled with the latest in SAW filter technology optimized to the specific frequency band of operation. This high gain version has an additional gain stage for the output. This design technology produces a LNA that is more selective and more robust in reducing out of band interference.

Both gain stages together employ a higher linear output that exceeds all other DEMI LNA products and coupled with a selective Saw filter between both stages, out of band interference is limited. The NBLNA's are housed in a 2.6" L x 1.5" W machined enclosure. Only the difference in connector selection will alter the length measurement. Any combination of Type "N", BNC or SMA connectors may be selected.

This new LNA design does not offer any RF bypass switching for transceiver operation and therefore may only be utilized in receive only applications. It is offered with various types of RF connectors and connector combinations. This NB series LNA is ready to be "dropped in" to any pre-existing receive system or to be a component in a newly developed receive system.

Schematic Diagram of NBLNAH Design:

